

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
6 February 2003 (06.02.2003)

PCT

(10) International Publication Number  
**WO 03/009925 A1**

- (51) International Patent Classification<sup>7</sup>: **B01D 53/94**, (74) Agent: **BEYER, Andreas**; Wuesthoff & Wuesthoff, FOIN 3/20 Schweigerstrasse 2, 81541 München (DE).
- (21) International Application Number: PCT/EP02/08097 (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 19 July 2002 (19.07.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 101 35 646.3 21 July 2001 (21.07.2001) DE
- (71) Applicant (*for all designated States except US*): **BALLARD POWER SYSTEMS AG** [DE/DE]; Neue Strasse 95, 73230 Kirchheim-Nabern (DE).
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): **BENZ, Uwe** [DE/DE]; Krummes Land, 88690 Oberuhldingen (DE). **KEPPELER, Berthold** [DE/DE]; Teckstrasse 45/6, 73277 Owen (DE). **MARTIN, André** [DE/DE]; Am Taubenberg 94, 65510 Idstein (DE). **SCHÜRSTEDT, Peter** [DE/DE]; Reussensteinweg 4, 73249 Wernau (DE). **zur MEGEDE, Detlef** [DE/DE]; Plochinger Strasse 92, 73230 Kirchheim (DE).
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: SYSTEM AND METHOD FOR REDUCING NITROGEN OXIDES IN THE EXHAUST OF AN INTERNAL COMBUSTION ENGINE

(57) Abstract: In a system and method for the reduction of nitrogen oxides in the exhaust of an internal combustion engine, the exhaust line of the internal combustion engine contains a DeNOx catalytic converter, in which the nitrogen oxides are reduced by means of hydrogen that is produced on-board the vehicle. The DeNOx catalytic converter is incorporated into a temperature-controlled heat exchanger, allowing the DeNOx catalytic converter to be operated within a desired temperature range, thereby improving the level of conversion.

WO 03/009925 A1

- 1 -

System and method for reducing nitrogen oxides  
in the exhaust of an internal combustion engine

5 Field of the Invention

The invention concerns a system and a method to reduce nitrogen oxides in the exhaust of an internal combustion engine.

10 Description of the Related Art

Due to excess air that is almost always present in diesel engine exhaust, it is not possible to completely eliminate all gaseous pollutants – such as carbon monoxide, hydrocarbons, and nitrogen oxides (NO<sub>x</sub>) – using the 3-way catalytic converters that have been state of the art technology for gasoline engines for years. Even though diesel engine exhaust contains some reducing substances, such as carbon monoxide and hydrocarbons, their concentration is not significant compared to the amount of nitrogen oxides to be reduced. Gasoline engines that run on a lean mixture are faced with the same problem. An additional problem is the comparatively low exhaust temperature.

Future exhaust emission standards require conversion levels of nitrogen oxides in the exhaust of higher than 80%, which has been very difficult to achieve.

25 One option for eliminating nitrogen oxides from exhaust is the selective catalytic reduction ("SCR") process, in which nitrogen oxides in the exhaust stream are catalytically and selectively reduced to nitrogen through the use of an added reducing agent, such as fuel, carbon monoxide, ammonia, urea, or hydrogen.

30 The conversion level of nitrogen oxides is not sufficient in a reduction process using only added fuel. In addition, this sometimes gives rise to strongly elevated hydrocarbon emissions. Providing an additional reducing agent, such as ammonia or urea, requires an additional tank and additional safety measures. Similar problems are encountered when hydrogen is carried in pressure tanks or tanks for liquids. For this reason, an attractive reducing agent, particularly for cold-start up, is presently seen to be hydrogen produced on-board thermally or catalytically from the same fuel used in the internal combustion engine.

- 2 -

EP 0 537 968 B1 describes a device to reduce nitrogen oxides in the exhaust of internal combustion engines. A DeNOx (nitrogen oxide removal) catalytic converter is included in the exhaust line. Hydrogen is produced by a hydrogen generator on-board the vehicle from the internal combustion engine fuel, and is introduced into the exhaust line upstream of the DeNOx catalytic converter. Using the fuel intended for the internal combustion engine eliminates the need for an additional tank, which would require additional space and result in additional weight.

However, there remains a need for improved systems and methods for reducing nitrogen oxides in the exhaust of internal combustion engines with an improved level of conversion.

#### BRIEF SUMMARY OF THE INVENTION

Using a heat exchanger design with active cooling of the DeNOx catalytic converter makes it possible to set a temperature level that is suitable for the reduction reaction in all operating states. This improves the selectivity of the reaction, which results in a higher level of conversion in the reduction of nitrogen oxides. At the same time, less hydrogen is needed, and thus less additional fuel, which lowers fuel consumption. Moreover, thermal control over the reaction in the DeNOx catalytic converter can be maintained even when large quantities of hydrogen are added.

The use of a temperature sensor enables very simple and accurate control of the temperature in the DeNOx catalytic converter. A multi-stage design of the DeNOx catalytic converter offers advantages with respect to the level of conversion of nitrogen oxides.

These and other aspects will be evident upon reference to the attached figure and following detailed description.

#### BRIEF DESCRIPTION OF DRAWING(S)

Figure 1 is a block diagram of an embodiment of the present system and method for the reduction of nitrogen oxides in the exhaust of internal combustion engines, in particular diesel and gasoline engines.

- 3 -

## DETAILED DESCRIPTION OF THE INVENTION

Referring to Figure 1, an internal combustion engine 1 is supplied with fuel from a fuel tank 2 through a first fuel line 3 and with air through an intake line 4. In internal combustion engine 1, fuel is combusted together with the air, and the resulting exhaust is discharged through an exhaust line 5.

Exhaust line 5 contains a DeNOx catalytic converter 6, in which nitrogen oxides contained in the exhaust are converted by a reducing agent at a suitable catalyst. Hydrogen or a hydrogen-rich gas is used as the reducing agent, and is introduced into exhaust line 5 upstream of DeNOx catalytic converter 6 through a hydrogen feed line 7. In addition to DeNOx catalytic converter 6, exhaust line 5 may contain other components (not shown), such as, for example, additional oxidation catalysts or an exhaust sound absorber.

The hydrogen or hydrogen-rich gas is produced on-board the vehicle in a hydrogen-generating reactor 8 from the fuel used in internal combustion engine 1. Fuel is supplied from fuel tank 2 to hydrogen-generating reactor 8 through a second fuel line 9. In hydrogen-generating reactor 8 (e.g. a reformer) the fuel is converted to a hydrogen-rich gas by means of well-known processes, possibly with the addition of further reactants such as water or an oxygen-containing medium. Preferably the hydrogen-rich gas produced is a synthesis gas, i.e. a mixture that consists predominantly of hydrogen and carbon monoxide. A gas purification and gas separation unit (not shown) may be provided between hydrogen-generating reactor 8 and DeNOx catalytic converter 6, so that a gas with higher hydrogen content or almost pure hydrogen can be supplied into exhaust line 5 through hydrogen feed line 7.

The reaction that takes place in hydrogen-generating reactor 8 preferably is a catalytic partial oxidation. However, in principle it is also possible to carry out – instead of or in addition to the partial oxidation – thermal pyrolysis (with the disadvantage of particulate soot formation) and/or steam reforming (with the disadvantage of requiring extra water). One or several subsequent shift stages can also be included, in order to increase the hydrogen concentration while simultaneously reducing the carbon monoxide content.

In DeNOx catalytic converter 6, nitrogen oxides in the exhaust are selectively reduced at the catalyst with the added hydrogen to produce nitrogen and water, so

- 4 -

that no, or only small amounts of, nitrogen oxides are discharged into the environment. Such DeNOx catalytic converters have been available for some time.

5 In a representative embodiment, DeNOx catalytic converter 6 is arranged on one side of a heat exchanger 10. Coolant is directed through the cooling side 11 of heat exchanger 10. This coolant is supplied to, and discharged from, cooling side 11 of heat exchanger 10 by way of a coolant line 12, which contains a valve 13. Preferably, valve 13 is located in coolant line 12 upstream of heat exchanger 10.

10 Preferably, the coolant is a gas, such as the intake air of the internal combustion engine, or air supplied by a fan. Other options include cooling by means of exhaust recirculation or cooling using the liquid coolant of the internal combustion engine. On cooling side 11 of heat exchanger 10, the coolant may be carried in countercurrent, co-current and/or cross-current flow with respect to the exhaust in DeNOx catalytic  
15 converter 6.

Valve 13 is used to control the coolant flow through cooling side 11 of heat exchanger 10, and thus the temperature in the catalytic reaction zone of DeNOx catalytic converter 6.

20 For this purpose, the illustrated embodiment includes a temperature sensor 15 in DeNOx catalytic converter 6. However, the temperature sensor may be located in exhaust line 5 downstream of DeNOx catalytic converter 6. Temperature sensor 15 provides a controller 14 with the measured temperature through an instrument lead  
25 16. On the basis of the measured temperature, controller 14 determines a suitable setting for valve 13 and relays it to valve 13 through a control line 17. This makes it possible to maintain the temperature in DeNOx catalytic converter 6 within a specified or desired temperature range during all operating states.

30 In another embodiment, a fan can be used to supply the cooling air and the fan speed can be varied in response to the temperature sensor 15 reading to adjust the desired coolant flow, eliminating the need for valve 13. Other devices that can be used as valve 13 include ventilating valves or conventional valves. Under the right circumstances, valve 13 may be eliminated entirely, such as in an optimized design of  
35 DeNOx catalytic converter 6 or if the hydrogen supply is optimized or controlled as a function of the load.

- 5 -

The required quantities of hydrogen can be produced in hydrogen-generating reactor 8 from the existing fuel. In contrast to the arrangement where fuel is supplied directly into the exhaust line, the separate production and introduction of hydrogen does not lead to additional hydrocarbon emissions, and only slightly increases fuel consumption. The composition of the hydrogen-containing gas (e.g. content of hydrogen, carbon monoxide, and/or methane) produced by hydrogen-generating reactor 8 can be matched to a certain degree to the requirements of DeNOx catalytic converter 6 by varying the operating parameters, thereby changing the thermodynamic equilibrium position. For this purpose, as shown in the representative embodiment in Figure 1, suitable measuring and control lines 18, 19 may be provided between hydrogen-generating reactor 8 and controller 14. Controller 14 may be equipped with additional monitoring inputs.

Hydrogen possesses a very high selectivity for NOx reduction at temperatures below 200°C, whereas it is almost completely combusted with the excess air at higher temperatures. The reaction of nitrogen oxide and hydrogen is an exothermic reaction, and part of the hydrogen and the carbon monoxide is usually oxidized by the oxygen that is present, which also releases heat. Consequently, if no active cooling is present, DeNOx catalytic converter 6 and the exhaust are heated by these reactions, reducing the selectivity for the reduction of nitrogen oxides.

In order to control the temperature of the DeNOx catalytic converter, DeNOx catalytic converter 6 is integrated with a cooling system 11 in a heat exchanger 10. This arrangement leads to active cooling of the DeNOx catalytic converter 6, which makes it possible – using a suitable adjustment of the coolant flow – to maintain DeNOx catalytic converter 6 within a specified or desired temperature range. Aside from the shown heat exchanger design, it is of course possible to use other known cooling elements to cool DeNOx catalytic converter 6. However, the temperature control for the DeNOx catalytic converter 6 of the present system and method makes it possible to always achieve a high selectivity for the reduction of nitrogen oxides. This allows the use of catalysts that possess sufficient selectivity in only a narrow temperature range.

The DeNOx catalyst material may be present in the form of catalytically active elements (e.g. pellets, fleece) or as a coating on reactor walls or installed component parts (e.g. turbulence generators, spacer elements). It is possible to vary the catalyst loading along the length of the reactor to adjust the thermal transfer properties and

- 6 -

the catalytic characteristics. This makes it possible to set a temperature profile suitable for the reaction.

5 Instead of the single-stage design of DeNOx catalytic converter 6 shown in the representative embodiment, the DeNOx catalytic converter may be of a multi-stage design. In such an embodiment, the reducing agent is introduced into the exhaust at several locations, always into an adiabatic stage, which is followed by intermediate cooling in a heat exchanger.

10 From the foregoing it will be appreciated that, although specific embodiments of the invention have been described herein for purposes of illustration, various modifications may be made without deviating from the spirit and scope of the invention. Accordingly, the invention is not limited except as by the appended claims.

15

## CLAIMS

5 1. A system to reduce nitrogen oxide emissions of an internal combustion engine having an exhaust line, the system comprising:

- a DeNOx catalytic converter in the exhaust line, the DeNOx catalytic converter having a reactor portion comprising a catalyst for the reduction of nitrogen oxides, and a temperature regulating portion,

10 - a hydrogen-generating reactor, and

- a hydrogen feed line connecting the hydrogen-generating reactor to the exhaust line upstream of the DeNOx catalytic converter.

15 2. The system of claim 1, further comprising a fuel tank, the fuel tank being connected to supply fuel to the hydrogen-generating reactor and the internal combustion engine.

20 3. The system of claim 1 wherein the internal combustion engine has a cooling system, and wherein the DeNOx catalytic converter is integrated with the engine cooling system.

4. The system of claim 1 wherein the temperature regulating portion of the DeNOx catalytic converter comprises one or more channels.

25 5. The system of claim 4 wherein the channels are connected to receive at least one of the intake air supplied to the internal combustion engine, an air stream supplied by a fan, and a partial exhaust stream being recirculated to the internal combustion engine.

30 6. The system of claim 4, further comprising a temperature sensor associated with the DeNOx catalytic converter, and a mechanism for adjusting the supply of coolant fluid to the channels in response to the temperature sensor.

35 7. The system of claim 6 wherein the mechanism for adjusting the supply of coolant fluid to the channels comprises a valve disposed in the coolant line and a controller associated with the valve and the temperature sensor for adjusting the supply of coolant fluid.



8. The system of claim 6 wherein the mechanism for adjusting the supply of coolant fluid to the channels comprises a controller for adjusting the speed of a device directing coolant fluid through the channels.

5 9. The system of claim 6 wherein the temperature sensor is disposed in the DeNOx catalytic converter.

10. The system of claim 6 wherein the temperature sensor is in the exhaust line downstream of the DeNOx catalytic converter.

10 11. The system of claim 1 wherein the DeNOx catalytic converter comprises at least two stages, each stage in the exhaust line, and wherein the hydrogen feed line is more than one hydrogen feed line with at least one hydrogen feed line connecting the hydrogen generating reactor to the exhaust line upstream of each stage.

15 12. A method of reducing nitrogen oxide emissions from an internal combustion engine, the method comprising:

20 (a) passing exhaust from the internal combustion engine through a DeNOx catalytic converter, and

(b) maintaining the temperature of the DeNOx catalytic converter within a desired temperature range by supplying a coolant fluid to a heat exchanger integrated with the DeNOx catalytic converter.

25 13. The method of claim 12 wherein the amount of coolant fluid supplied to the heat exchanger is adjusted based on a parameter indicative of the temperature of the DeNOx catalytic converter.

30 14. The method of claim 13, further comprising monitoring the temperature in the DeNOx catalytic converter.




Fig. 1

## INTERNATIONAL SEARCH REPORT

Int'l Application No

PCT/EP 02/08097

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 B01D53/94 F01N3/20

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 B01D F01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 947 683 A (HERAEUS ELECTRO NITE INT) 6 October 1999 (1999-10-06) claims 16-26	12-14
A	paragraphs '0012!-'0017!; claims 1-15; figure 2	1-11
X	EP 0 881 366 A (DEGUSSA) 2 December 1998 (1998-12-02)	12-14
Y	(in combination with EP0537968) the whole document	1-11
Y	EP 0 537 968 A (TOYOTA MOTOR CO LTD) 21 April 1993 (1993-04-21) cited in the application column 4, line 32 -column 7, line 25; claims; figure 1	1-11
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*&\* document member of the same patent family

Date of the actual completion of the international search

24 October 2002

Date of mailing of the international search report

30/10/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Fourgeaud, D

## INTERNATIONAL SEARCH REPORT

Int l Application No  
PCT/EP 02/08097

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 1 094 206 A (NISSAN MOTOR) 25 April 2001 (2001-04-25) (in combination with US 5477676) claims; figures 2,17-19 ----	1-14
Y	US 5 477 676 A (BENSON DAVID K ET AL) 26 December 1995 (1995-12-26) column 2, line 39 -column 3, line 12; claims; figures ----	1-14
A	US 4 033 133 A (HOUSEMAN JOHN ET AL) 5 July 1977 (1977-07-05) column 3, line 4 -column 7, line 5; figure 1 ----	1-14
A	US 5 921 076 A (GOERIGK CHRISTIAN ET AL) 13 July 1999 (1999-07-13) claims; figures 1,2 -----	1-14

# INTERNATIONAL SEARCH REPORT

information on patent family members

Int'l Application No

PCT/EP 02/08097

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0947683	A	06-10-1999	BR 9902023 A EP 0947683 A2 JP 11324659 A US 6202406 B1	22-02-2000 06-10-1999 26-11-1999 20-03-2001
EP 0881366	A	02-12-1998	DE 19721439 A1 DE 59802685 D1 EP 0881366 A2 JP 11050838 A US 5934073 A	28-01-1999 21-02-2002 02-12-1998 23-02-1999 10-08-1999
EP 0537968	A	21-04-1993	JP 5106430 A DE 69207854 D1 DE 69207854 T2 EP 0537968 A1 US 5412946 A	27-04-1993 07-03-1996 05-06-1996 21-04-1993 09-05-1995
EP 1094206	A	25-04-2001	JP 2001234737 A EP 1094206 A2	31-08-2001 25-04-2001
US 5477676	A	26-12-1995	US 5318108 A US 5157893 A US 5175975 A BR 9506649 A CA 2182016 A1 CN 1144551 A ,B EP 0832346 A1 JP 2821582 B2 JP 9511558 T KR 175719 B1 WO 9520721 A1 AU 3655993 A WO 9409333 A1 US 5562154 A US 5433056 A US 5643485 A US 5813454 A AT 143084 T AU 662294 B2 AU 8228991 A DE 69122249 D1 DK 535147 T3 EP 0535147 A1 ES 2091935 T3 GR 3021712 T3 JP 3045543 B2 JP 5509381 T WO 9119867 A1 AU 645481 B2 AU 3559089 A CA 1328724 A1 DE 68928547 D1 DE 68928547 T2 EP 0425499 A1 JP 2736468 B2 JP 4503701 T WO 8909860 A1 US 5107649 A	07-06-1994 27-10-1992 05-01-1993 02-09-1997 03-08-1995 05-03-1997 01-04-1998 05-11-1998 18-11-1997 20-03-1999 03-08-1995 09-05-1994 28-04-1994 08-10-1996 18-07-1995 01-07-1997 29-09-1998 15-10-1996 31-08-1995 07-01-1992 24-10-1996 13-01-1997 07-04-1993 16-11-1996 28-02-1997 29-05-2000 22-12-1993 26-12-1991 20-01-1994 03-11-1989 26-04-1994 19-02-1998 23-04-1998 08-05-1991 02-04-1998 02-07-1992 19-10-1989 28-04-1992

# INTERNATIONAL SEARCH REPORT

information on patent family members

Int. Application No

PCT/EP 02/08097

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4033133	A	05-07-1977	NONE	
US 5921076	A	13-07-1999	DE 19600558 A1	10-07-1997
			DE 59608596 D1	21-02-2002
			EP 0783918 A1	16-07-1997